

Statistics

	Average	Maximum	Minimum	Max/Min	Avg/Min
INFIELD	51.1	63.6	33.5	1.9	1.5
OUTFIELD	32	44.9	19	2.4	1.7

These lighting calculations are not a substitute for an independent engineering analysis of lighting system suitability and safety.

Luminaire Schedule


Symbol	Qty	Catalog No.	Lamp	Initial Lumens
N	36	ASPX5M GN	MH1500/BU-HOR	151900
M	10	ASPX5M GM	MH1500/BU-HOR	151900
W	2	ASPX5M GW	MH1500/BU-HOR	151900

Notes

- 1) Levels shown are maintained horizontal illuminance.
- 2) Based on a light loss factor of .80
- 3) Results are shown in units of footcandles.
- 4) Levels shown are taken 3 Feet above grade.
- 5) Includes effects of lamp operating position.
- 6) EPA does not include bracketry
- 7) Levels based on rated input voltage supplied to ballast

Luminaire Legend

Pole	Quantity	EPA[FT SQ]	Power[KVA]	Height
A1	8	26.4	12.88	60
A2	8	26.4	12.88	60
B1	8	26.4	12.88	70
B2	8	26.4	12.88	70
C1	8	26.4	12.88	70
C2	8	26.4	12.88	70



Drawing Number:	BB653AS	Drawn By:	
		Approved:	
Sheet 1 of 1		Date: 10/13/03	
		Scale: 1 Inch = 100 Feet	

TYPICAL 300FT BASEBALL FIELD
6 POLE 50/30FC LAYOUT